

检验号 18B0079

产品质量证明书

INSPECTION CERTIFICATE


订货单位: 靖江市亚泰物流装备有限公司 Customer:		产品名称: 不锈钢热轧钢带 Product: Hot rolled stainless steel coil		
收货单位: 靖江市亚泰物流装备有限公司 Purchaser:		交货状态: 1D/No.1 固溶 酸洗 切边 Condition: 1D/No.1:Solid solution;Pickling;C		
标准Specification SANS50028-7:2005 EN10028-7:2007 ASME SA-240M-2015	牌号Grade 1.4404/1.4402 1.4404/1.4401 316L/316	合同号Mill'S No. 757227-20 客户订单Customer Order No.	证书编号Certificate No. 1344922846259285 提单号Consignment No. NEW8009204001 车号Train Wagon No. 晋AU1888	

序号 No.	材料号 Material No.	炉号 Heat No.	规格 Dimensions (mm)	数量 Quantity	重量 Weight(t)
1	FA80602090N00	A2802257	6*1425	1	23.940
尺寸及外观Acceptable Visual And Dimensions:合格OK 合计Total 1 23.940					

序号 No.	分析 Max. Min.	C%	Si%	Mn%	P%	S%	Cr%	Ni%	Mo%	N%
1	H	0.023	0.59	1.10	0.031	0.001	17.06	10.28	2.14	0.06

序号 No.	位置 方向 P.D.	屈服强度 Y.S. Rp0.2 Mpa 常温	屈服强度 Y.S. Rp1.0 Mpa 常温	抗拉强度 T.S. Rm Mpa 常温	伸长率 EL. A5 % 常温	伸长率 EL. A50 % 常温	屈服强度 Y.S. Rp0.2 Mpa 130℃	屈服强度 Y.S. Rp1.0 Mpa 130℃	抗拉强度 T.S. Rm Mpa 130℃	伸长率 EL. % 130℃	硬度 Hardness HRB 常温	硬度 Hardness HRB HRB	晶间腐蚀 IG C
1	2	298	339	590	55	56.5	245	285	515	50.5	80.5	80.5	OK

注释 Notes	C=Cutting edge; H=熔炼分析Heat analysis; P=成品分析Product analysis; Y.S.=Yield Strength; 常温 = Normal Temperature (Room Temperature); T.S.=Tensile Strength; EL.=Elongation; A5:Lo=5.65SQRT(So); A50:Lo=50mm; 2=横向Transverse;
声明 Declare	本产品仅限国内销售不得出口, 经销商向用户出具本质量证明书复印件需加盖其公章。This product is for domestic sales in China only. Export is not allowed. This certificate, if provided by a re-seller in photocopy, is invalid unless with the re-seller's company stamp.
备注 Remarks	



声明: 本产品已按上述要求制造和检验, 结果符合要求, 特此证明。
We Hereby Certify That Material Described Herein Has Manufactured And Tested With Satisfactory Results In Accordance With The Requirements Of The Above Material Specification.



中国 山西 太原市尖草坪街2号 邮编030003
Jiancaoping, Taiyuan, Shanxi, P.R. China. zip code 030003
服务热线 After-sale Service: 800-806-1998, 400-653-1998

NAN HAI
质量负责人 Quality Manager

材料号 180079-1

产品质量证明书
INSPECTION CERTIFICATE

订货单位: 靖江市亚泰物流装备有限公司 Customer:		产品名称: 不锈钢热轧钢带 Product: Hot rolled stainless steel coil		
收货单位: 靖江市亚泰物流装备有限公司 Purchaser:		交货状态: 1D/No.1 固溶 酸洗 切边 Condition: 1D/No.1: Solid solution; Pickling; C		
标准 Specification SANS50028-7:2005 EN10028-7:2007 ASME SA-240M-2015	牌号 Grade 1.4404/1.4402 1.4404/1.4401 316L/316	合同号 Mill's No. 750925-10 客户订单 Customer Order No.	证书编号 Certificate No. 1344922846248148 提单号 Consignment No. NEW8009201001 车号 Train Wagon No. 晋KB6718	

序号 No.	材料号 Material No.	炉号 Heat No.	规格 Dimensions (mm)	数量 Quantity	重量 Weight(t)
1	FA80603940N00	A2802257	6*1425	1	22.390
18B0079-1					
尺寸及外观 Acceptable Visual And Dimensions: 合格 OK			合计 Total	1	22.390

序号 No.	分析 Max. Min.	C%	Si%	Mn%	P%	S%	Cr%	Ni%	Mo%	N%
1	H	0.023	0.59	1.10	0.031	0.001	17.06	10.28	2.14	0.06

序号 No.	位置 方向 P.D.	屈服强度 Y.S. Rp0.2 Mpa 常温	屈服强度 Y.S. Rp1.0 Mpa 常温	抗拉强度 T.S. Rm Mpa 常温	伸长率 EL. A5 % 常温	伸长率 EL. A50 % 常温	屈服强度 Y.S. Rp0.2 Mpa 130℃	屈服强度 Y.S. Rp1.0 Mpa 130℃	抗拉强度 T.S. Rm Mpa 130℃	伸长率 EL. % 130℃	硬度 Hardness HRB 常温	硬度 Hardness HRB HRB	晶间腐蚀 IG C
1	2	295	329	601	57.5	57.5	245	285	500	48.5	83.5	84	OK

注释 Notes	C=Cutting edge; H=熔炼分析 Heat analysis; P=成品分析 Product analysis; Y.S.=Yield Strength; 常温 = Normal Temperature (Room Temperature); T.S.=Tensile Strength; EL.=Elongation; A5:Lo=5.65SQRT(So); A50:Lo=50mm; 2=横向 Transverse;
声明 Declare	本产品仅限国内销售不得出口, 经销商向用户出具本质量证明书复印件需加盖其公章。This product is for domestic sales in China only. Export is not allowed. This certificate, if provided by a re-seller in photocopy, is invalid unless with the re-seller's company stamp.
备注 Remarks	

